

**Transmitter  
AT GENIO-PUNTO**



**GENIO-PUNTO**


**Receiver  
AR GENIO FLEXI A**



**GENIO A**



**BOARD**



## CONFIGURATIONS

Version	Transmitter	Receiver
<i>GENIO-PUNTO GR</i>	2 dual axis Joystick up to 4 steps + up to 6 on/off commands + Key switch + Start/Clacson + Stop	Cableglad or connector output (VAC or VDC power supply)
<i>GENIO-PUNTO (on/off)</i>	Up to 22 on/off commands + Key switch/Start/Clacson + Stop	Cableglad or connector output (VAC or VDC power supply)

## TECHNICAL DETAILS

Transmitter	AT GENIO.H PUNTO	AT GENIO-K PUNTO	Receiver	GENIO FLEXI A	GENO A	BOARD
Frequency range	433.050 – 434.050 434.050 – 434.790 MHz	869.700 – 870.000 MHz	Power supply	24/48/55 VAC 50/60 Hz	24/48/55/110/230 VAC 50/60 Hz	18-24 VAC 50/60 Hz o 24 VDC
RF-output power	< 10 mW ERP	< 5 mW ERP	Absorbed power	<18 VA	< 35VA	<10W
Typical range	Approx. 150 meters		N° max channels	14 on/off	21 on/off	6 on/off (expandable)
Temperature range	from -20°C to +55°C		Antenna	Internal		External (optional)
Autonomy at 20°C	Approx. 20 hours		Protection class	IP54	IP44	-
Antenna	Internal		Size	155x255x85 mm	170x500x90 mm	110x200x90 mm
Protection class	IP54		Weight	1,2 Kg	3,6 Kg	0,8 Kg
Size	172x130x125 mm		Housing	ABS plastic compound		DIN bar support
Weight	1,1 Kg		<b>Battery charger</b>	CONTROL-GEA	CONTROL-GED	
Housing	ABS plastic compound		Power supply	80-250 VAC; 50/60 Hz		9-30 VDC
Push button command	Up to 4 commands for each joystick		With charging control system			
Self-stopping device	After 8 minutes of no use (excluded as optional)					
<b>Batteries</b>	PINC-GE					
Type	NiCd					
Capacity	7,2V – 0,7Ah					

Automatic frequency change system

**CE DIRECTIVE:** 99/05/CE regarding radio equipment and telecommunications terminals equipment and the mutual recognition of their conformity. Authorization obtained also in extra EU countries. Specifications and design are subject to change without notice.