



Mini Transmitter

Compact but packed with functionality

The Mini is a compact and versatile transmitter that can easily be customized to suit your requirements. With its modular design, the Mini can accommodate 1-6 linear levers or 1-3 joysticks as well as several pushbuttons and switches. Despite the compact format, all controls are sized and positioned to support daily usage for many hours without causing operator fatigue.

The transmitter has a bundle of both standard and optional settings and features to improve the operator experience. The maximum speed of proportional movements can be adjusted using a “turtle/rabbit” toggle switch in five steps. A graphic display and/or LEDs enable operator feedback from the controlled machine. Automatic frequency management allows for continuous operation without any interruptions caused by radio interference from other wireless equipment. The on-site calibration feature allows authorized users to change and adjust system settings without any external tools or software.

The transmitter communicates with the corresponding receiver using a Scanreco protocol and a unique identity code. This guarantees that no other Scanreco transmitter or other product can ever activate the machine unintentionally. The stop function conforms to performance level “e” (PL e), the highest level specified by EN ISO 13849-1, a legally binding standard for safety-critical components of control systems.

The Mini transmitter is designed for heavy-duty use and we know that our customers rely on our ability to deliver functionality they can trust – we call this Never-Stop Technology™ from Scanreco.

This is the Mini transmitter

- » 1-6 linear levers or 1-3 joysticks
- » Various toggle switches, pushbuttons and rotary switches
- » Feedback through LEDs and/or a graphic display
- » Stop function in accordance with EN ISO 13849-1 cat. 3, PL e
- » Operational time: approx. 10 hours on a single charge
- » Frequency bands: 433-434 or 902-928MHz (other frequencies available on request)
- » Operating range < 100m / < ~330 ft.
- » Cable control: Standard Length 10 meters / ~33 ft.
- » Operational temperature: -25°C to +70°C / ~-15°F to +160°F
- » Protection category: IP65
- » Dimensions: (W x H x D): 290 x 160 x 190 mm / ~11.42 x 6.30 x 7.48 in
- » Weight: 1.4–1.8 kg / ~3.1–3.9 lbs. including battery

