

# SE889/K2.3



- ✓ 100% KAYS compatible, applicable for most types of cranes
- ✓ Easy mounting and adaption
- ✓ Robust and reliable
- ✓ Compact and easy to service
- ✓ Can be combines with all Gross Funk transmitter types
- ✓ Optional extension modules

Dimensions (LxWxH mm)	310x160 x90
Weight (ca. depending on equipment)	3500 gr.
IP-protection class	IP65
Power supply (pls. indicate in your order)	12/24V DC 24/48/11 5/230 V AC
Automatic 12/24V switch	✘
Operating temperature	-20 - +60°C
Safety class (DIN19250)	AK5
DIN rail assembly	✘
Aluminium receiver box	✓
Number of digital functions (basis equipment)	20
Number of analogue outputs per extension module	6
Number of PWM outputs per extension module	6
Number of digital inputs per extension module	7
Number of analogue inputs per extension module	2

Max. resolution of the analogue inputs	12BIT
Max. resolution of the analogue outputs	12BIT
Serial interface (optional)	RS232, RS485
Serial interface (already on board)	✘
BUS capable (optional)	✓
Extendable	✓
Frequency switch	✓
Reflektomat	✓
Frequency hopping	✓
Transceiver (bi-direction. radio path)	✓
Multiple transmitting operation	✓
Multiple receiving operation	✓
Receiver stand-by	✘
Adapter for charger on receiver box	✓