



## Compact Transmitters T07

The small, handy transmitter for your application shines with its comfortable carrying method.

- compact and robust casing
- impact resistant, heat resistant and waterproof
- available in almost all standard forest control variants
- optional stand-by automatic saves the battery
- for analog and digital applications
- ergonomically corrugated railing for easy access to switch positions
  - also available as [Atex control unit](#)

### Technical data

Standard = √ Optional = O

IP protection class	IP65
Transmitter power 10mW	O
Frequency range 433/434 MHz	O
Frequency range 868 MHz	O

### Device data

Dimensions (LxWxH mm) (if necessary plus attachment)	126x13x48
Weight (approx. depending on equipment)	400g
Operation temperature	-20 bis 60°C

# Gross Funk<sup>®</sup>

## Transmitter information

Standard = √ Optional = O	
Emergency stop switch	O
Joystick	Ottocontroll s/w oder Hall analog
Toggle switch	O
Button (1-u. 2- steps)	O
Potentiometer	O
Rotary switch	O
LED 3/5 and 8	O
Audible signal generator	O
Frequency	O
Transceiver (bi-direction radio path)	O
Multiple transmitting operation	O
Tandem operation	O
Stand-By Automatic	O

## Power supply

Battery	2 copies included with the transmitter
Voltage	7,2V
Battery life	Depending on use max. 10h
Recharge	Plug versions for: EU / UK / US /AUT

## Display versions

No display available