





### Compact

# **Transmitter T23**

# The T23 belongs to our compact transmitters

Despite the compact design, very flexible in use

- the stainless steel railing protects the switches from unintentional operation
- compact yet easy to use

Device data

• easy to operate even with gloves



#### Technical data

Standard = $\sqrt{\text{Optional}} = O$		Dimensions (LxWxH mm) (if necessary plus	263x109x133
IP protection class	IP65	attachment)	
		Weight (approx. depending on equipment)	1200g
Transmitter power 10mW	0		
Frequency range 433/434 MHz	0	Operation temperature	-20 bis 60°C
Frequency range 868 MHz	0		



### Transmitter information

#### Power supply

Standard = $$ Optional = O		
Emergency stop switch	Ο	
Joystick	0	
Masterswitch 1-u. 2-axial	0	
Toggle switch	Ο	
Button (1-u. 2-steps)	Ο	
Potentiometer	0	
Rotary switch	0	
LED 3/5 and 8 mm	Ο	
Audible signal generator	Ο	
Frequency	0	
Transceiver (bi-direction radio path)	Ο	
Multiple transmitting operation	0	
Tandem operation	0	
Stand-By Automatic	0	

Battery	2 copies included with the transmitter
Volatge	7,2V
Battery Life	depending on use max. 10h
Recharge	Plug versions for: EU / UK / US /AUT

#### Display versions

No display available