

Pult-Transmitter T85



Here you see, with the GF-T85, the largest transmitter from Gross Funk

The transmitter impresses with its large, flexible surface area and robust design.

- large control panel with plenty of space
- robust, solid and ergonomic
- arrangement of the control elements according to your wishes
- labeling in many languages and/or with symbols
- breastplate or stand for comfortable operation

Technical data

Standard = √ Optional = O	
IP protection class	IP65
Transmitter power 10mW	O
Transmitter power 100mW	O
Frequency range 433/434 MHz	O
Frequency range 868 MHz	O

Device data

Dimensions (LxWxH mm) (if necessary plus attachment)	442x305x485
Weight (approx. depending on equipment)	6500g
Operation temperature	-20 bis 60°C

Gross Funk®

Transmitter information

Standard = √ Optional = O	
Emergency stop switch	O
Joystick	O
Masterswitch 1-u. 2-axial	O
Toggle switch	O
Button (1-u. 2-steps)	O
Potentiometer	O
Rotary switch	O
Membrane keyboar	O
LED 3/5 and 8 mm	O
Audible signal generator	O
Frequency	O
Transceiver (bi-direction radio path)	O
Multiple transmitting operation	O
Tandem operation	O
Stand-By Automatic	O
Illuminated panel display	O

Power supply

Battery	2 copies included with the transmitter
Voltage	12V
Battery life	depending on use max. 10h
Recharge	Plug versions for: EU / UK / US /AUT

Display versions

Standard = √ Optional = O	
Videodisplay	O
LCD Display	2×8 characters/ O 2×16 characters/ O 4×20 characters/ O
Display 2,7" QVGA	(320×240) TFT / O (320×240) TFT, Transflective/ O
Display 4,3" WQVGA, Transflective	O
LED 7-Segment display	O